



# INDUSTRIAL BATTERIES

## RICO

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity 6 Hr. Rate		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
				KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
CBR-EX, HLB-EX, HLR-EX HRR-EX-60, RR-EX RR-EX-40, WCB-EX, WR-EX 36.5 x 13 x 32.75	24	12-D125-13	EX	17.46	750	125	3366	36.5	13	32.75	1577	X		Mounted	0	N7869
HLW-EX-10, HLW-EX-30 HLW-EX-50, PWH-EX-100 PWH-EX-120, PWH-EX-80 36.5 x 13.5 x Open	24	12-D125-13	EX	17.46	750	125	3366	36.5	13	32.75	1577	X		Mounted	0	N7869
HLW-EX-20, PWH-EX-40 PWH-EX-60 36.625 x 13.5 x Open	24	12-D85-13	EX	11.87	510	85	3389	36.625	13	25.5	1162	X		Mounted	0	N7869
HLR-EX, PLL-WR-EX-40 R-PT-R-EX 36.6875 x 13 x 25.5	24	12-D85-13	EX	11.87	510	85	3389	36.625	13	25.5	1162	X		Mounted	0	N7869
WCW-2500-EX 36.6875 x 13 x 27.125	24	12-D100-13	EX	13.97	600	100	3390	36.625	13	27.0625	1308	X		Mounted	0	N7869
SDEX-60, SDEX-80 37.0625 x 25.9375 x 24.1875	36	18-D85-19	EX	26.71	765	85	6205	37.0625	25.9375	24.125	2476	X		Mounted	0	N7869
SD-EX-80 37.0625 x 25.9375 x 27.1875	36	18-D100-19	EX	31.43	900	100	6A09	37.0625	25.9375	27.125	2786	X		Mounted	0	N7869

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type		Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads		Standard Conn.
				6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	Length (in.)	
DSD-EX-40, DSD-EX-60 DSD-EX-80 39 x 27.5 x 23.75 See Note A	36	18-D85-23	EX	32.65	935	85	6929	38.25	27	23.75	2927	X		Mounted	0	N7869
DSD-EX-60 Truck includes special EX battery compartment for standard battery construction 39 x 27.5 x 23.5	36	18-D85-23		32.65	935	85	6009	38.1875	26.9375	22.6875	2703		X	B	20	SB6320
	36	18-H80-23		30.73	880	80	6009	38.1875	26.9375	22.6875	2595		X	B	20	SB6320
	36	18-P95-23		36.49	1045	95	6009	38.1875	26.9375	22.6875	2730		X	B	20	SB6320
DSD-EX-60 Truck includes special EX battery compartment for standard battery construction 39 x 27.5 x 23.5625	36	18-D85-23		32.65	935	85	6022	38.1875	26.9375	23.5625	2781	X		B	20	SB6320
	36	18-H80-23		30.73	880	80	6022	38.1875	26.9375	23.5625	2670	X		B	20	SB6320
	36	18-P95-23		36.49	1045	95	6022	38.1875	26.9375	23.5625	2809	X		B	20	SB6320
Pegasus P-300 39.25 x 29.75 x Open See Note B	72	18-D85-23		32.65 ea	935	85	6022	38.1875	26.9375	23.5625	2781	X		B	24	SB6320
	72	18-H80-23		30.73 ea	880	80	6022	38.1875	26.9375	23.5625	2670	X		B	24	SB6320
	72	18-P95-23		36.49 ea	1045	95	6022	38.1875	26.9375	23.5625	2809	X		B	24	SB6320
HLS-R 36.5 x 13.5 x 33	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6320
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6320
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6320
HLS-R 39 x 16 x 33	36	18-D125-13		26.19	750	125	6137	38.125	15.6875	31.4375	2212	X		B	24	SB6320
	36	18-H120-13		25.14	720	120	6137	38.125	15.6875	31.4375	2190	X		B	24	SB6320
	36	18-P140-13		29.33	840	140	6137	38.125	15.6875	31.4375	2234	X		B	24	SB6320
PR 31.5 x 13.5 x Open	24	12-D125-13		17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6320
	24	12-H120-13		16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6320
	24	12-P140-13		19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6320
PWH 31.5 x 13.5 x Open	24	12-D100-13		13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6325
PR 38.5 x 16 x Open	36	18-D85-13		17.81	510	85	6031	37.6875	15.4375	23.5	1547	X		B	24	SB6320
	36	18-H80-13		16.76	480	80	6031	37.6875	15.4375	23.5	1485	X		B	24	SB6320
	36	18-P95-13		19.90	570	95	6031	37.6875	15.4375	23.5	1562	X		B	24	SB6320

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.
			KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)	
PWH 38.5 x 16 x Open	36	18-D85-13	17.81	510	85	6031	37.6875	15.4375	23.5	1547	X		B	24	SB6320
	36	18-H80-13	16.76	480	80	6031	37.6875	15.4375	23.5	1485	X		B	24	SB6320
	36	18-P95-13	19.90	570	95	6031	37.6875	15.4375	23.5	1562	X		B	24	SB6320
PLW-WR 31.5 x 13.5 x Open	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6325
PLR 31.5 x 13.5 x Open	24	12-D125-13	17.46	750	125	3008	30.5625	12.75	31.125	1455	X		B	20	SB6320
	24	12-H120-13	16.76	720	120	3008	30.5625	12.75	31.125	1440	X		B	20	SB6320
	24	12-P140-13	19.56	840	140	3008	30.5625	12.75	31.125	1470	X		B	20	SB6320
PLR 38.5 x 16 x Open	36	18-D85-13	17.81	510	85	6031	37.6875	15.4375	23.5	1547	X		B	24	SB6320
	36	18-H80-13	16.76	480	80	6031	37.6875	15.4375	23.5	1485	X		B	24	SB6320
	36	18-P95-13	19.90	570	95	6031	37.6875	15.4375	23.5	1562	X		B	24	SB6320
PLR-T-SB 41.25 x 18.5 x Open See Note B	72	18-D125-15	30.56 <sup>ea</sup>	875	125	6207	38.1875	17.8125	31.1875	2542	X		B	24	SB6320
	72	18-H120-15	29.33 <sup>ea</sup>	840	120	6207	38.1875	17.8125	31.1875	2517	X		B	24	SB6320
	72	18-P140-15	34.22 <sup>ea</sup>	980	140	6207	38.1875	17.8125	31.1875	2567	X		B	24	SB6320
PLR-T-SB 41.25 x 23.5 x Open See Note B	72	18-D125-19	39.29 <sup>ea</sup>	1125	125	6174	38.1875	22.3125	31.4375	3196	X		B	24	SB6320
	72	18-H120-19	37.71 <sup>ea</sup>	1080	120	6174	38.1875	22.3125	31.4375	3164	X		B	24	SB6320
	72	18-P140-19	44.00 <sup>ea</sup>	1260	140	6174	38.1875	22.3125	31.4375	3228	X		B	24	SB6320
R-LPRH 31.5 x 13.5 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6325
HLW 36.5 x 13.5 x Open	24	12-D100-13	13.97	600	100	3015	30.5625	12.75	26.25	1185	X		B	20	SB6325
HLW 39 x 16 x Open	36	18-D100-13	20.95	600	100	6214	37.6875	15.4375	26.25	1739	X		B	24	SB6320
R-LT-S 31.5 x 13.5 x Open	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6325
RJ-GT 31.5 x 13.5 x Open	24	12-D85-13	11.87	510	85	3019	30.5625	12.75	23.25	1049	X		B	20	SB6325
	24	12-H80-13	11.17	480	80	3019	30.5625	12.75	23.25	1007	X		B	20	SB6325
	24	12-P95-13	13.27	570	95	3019	30.5625	12.75	23.25	1059	X		B	20	SB6325

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

Truck Model and Maximum Battery Size (Inches)	Volt	Battery Type	Capacity		AH/ Pos. Plate	IST Tray No.	Battery Dimensions (in.)			Approx. Serv. Wt. (lbs.)	Cover		Leads Length		Standard Conn.	
			6 Hr. Rate KWH	A.H.			Length X	Width Y	Height Z		Yes	No	Pos.	(in.)		
R-LT-S-EE 30.5625 x 12.75 x 23.5 See Note C	24	12-D85-13	EE	11.87	510	85	3132	30.5625	12.75	23.5	1048	X		B	22	SB6325
	24	12-H80-13	EE	11.17	480	80	3132	30.5625	12.75	23.5	1006	X		B	22	SB6325
	24	12-P95-13	EE	13.27	570	95	3132	30.5625	12.75	23.5	1058	X		B	22	SB6325
R-TV-C 31.5 x 13.5 x Open See Note C	24	12-D85-13	EE	11.87	510	85	3132	30.5625	12.75	23.5	1048	X		B	20	SB6325
	24	12-H80-13	EE	11.17	480	80	3132	30.5625	12.75	23.5	1006	X		B	20	SB6325
	24	12-P95-13	EE	13.27	570	95	3132	30.5625	12.75	23.5	1058	X		B	20	SB6325
PRSS-40 31.5 x 13.5 x Open See Note D	24	12-D85-13	EE	11.87	510	85	3242	30.5625	12.75	23.25	1043	X		C	25	SB6325
	24	12-H80-13	EE	11.17	480	80	3242	30.5625	12.75	23.25	1001	X		C	25	SB6325
	24	12-P95-13	EE	13.27	570	95	3242	30.5625	12.75	23.25	1053	X		C	25	SB6325

EX - Explosion-proof battery and tray design.

EE - Spark-proof battery and tray design.

ea - KWH calculated for each 18-cell battery.

H - Designates (H-Series battery type). Hydrasaver Product - Extended Watering Series.

Note A - Special Explosion-proof tray IST6929 includes a battery fusebox mounted on the front side and extends 7.625 beyond the footprint width dimension of 27 shown. Overall width including fusebox is 34.625.

Note B - 72 volt Pegasus P-300 and PLR-T-SB model trucks require two (2) 18 cell batteries.

Note C - Special Spark-proof tray IST3132 includes cable exit holes located 4.5 from end of tray to first hole.

Note D - Special Spark-proof tray IST3242 includes cable exit holes located 2.625 from end of tray to first hole.

**Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.**

**EAST PENN manufacturing co., inc.**

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212  
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

**DISCLAIMER:** When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.