



INDUSTRIAL BATTERIES

CROWN

WALKIE, RIDER/WALKIE, TOW TRACTORS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. | |
|---|------|--------------|---------------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|-------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | | |
| GPW See Note A 25.625 x 8.875 x 24 | 24 | 12-D85-5 | 3.96 | 170 | 85 | 3167 | 24.25 | 8.3125 | 23.1875 | 464 | X | | A | 21 | SB 6325 | w/945 |
| | 24 | 12-H80-5 | 3.72 | 160 | 80 | 3167 | 24.25 | 8.3125 | 23.1875 | 445 | X | | A | 21 | SB 6325 | w/945 |
| | 24 | 12-P95-5 | 4.42 | 190 | 95 | 3167 | 24.25 | 8.3125 | 23.1875 | 469 | X | | A | 21 | SB 6325 | w/945 |
| | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3042 | 25.25 | 8.5625 | 23.1875 | 567 | X | | A | 21 | SB 6325 | w/945 |
| | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3042 | 25.25 | 8.5625 | 23.1875 | 544 | X | | A | 21 | SB 6325 | w/945 |
| | 24 | 12-P95-7 | 6.63 | 285 | 95 | 3042 | 25.25 | 8.5625 | 23.1875 | 573 | X | | A | 21 | SB 6325 | w/945 |
| 15WB, 20W, 20WR, 30W 30WA, 40W 35.0625 x 6.625 x 23.25 | 24 | 12-D85-5 | 3.96 | 170 | 85 | 3301 | 33.0625 | 6.4375 | 22.75 | 496 | | X | See Note B | | SB 6325 | w/945 |
| | 24 | 12-D85-5 | 3.96 | 170 | 85 | 3068 | 24.75 | 6.4375 | 22.5625 | 412 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-5 | 3.72 | 160 | 80 | 3301 | 33.0625 | 6.4375 | 22.75 | 476 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-5 | 3.72 | 160 | 80 | 3068 | 24.75 | 6.4375 | 22.5625 | 396 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-5 | 4.42 | 190 | 95 | 3301 | 33.0625 | 6.4375 | 22.75 | 501 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-5 | 4.42 | 190 | 95 | 3068 | 24.75 | 6.4375 | 22.5625 | 416 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3079 | 33.5625 | 6.4375 | 22.5625 | 567 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3079 | 33.5625 | 6.4375 | 22.5625 | 544 | X | | See Note B | | SB 6325 | w/945 |
| 20W, 20WB, 20WR, 25WB 30W, 30WA, 30WB, 30WR 40W, 40WB 31.75 x 13.125 x 23.25 | 24 | 12-D85-11 | 9.89 | 425 | 85 | 3041 | 26.0625 | 12.75 | 22.625 | 869 | | X | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-11 | 9.31 | 400 | 80 | 3041 | 26.0625 | 12.75 | 22.625 | 834 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-11 | 11.06 | 475 | 95 | 3041 | 26.0625 | 12.75 | 22.625 | 878 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3082 | 30.5625 | 12.75 | 22.625 | 1025 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3082 | 30.5625 | 12.75 | 22.625 | 984 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3082 | 30.5625 | 12.75 | 22.625 | 1035 | X | | See Note B | | SB 6325 | w/945 |
| 20WBTF, 20WBTL, 30WBTF 30WBTL, 30WBTT, 40WBTF 40WBTL, 40WBTT 31.75 x 13.1875 x 23.25 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | A | 17 | SB6325 | |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | A | 17 | SB6325 | |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | A | 17 | SB6325 | |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. | |
|---|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|---------------|-----------------|-------------------|-------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. (in.) | Length (in.) | | |
| ES4000 25.4375 x 8.6875 x 24.9375 | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3A95 | 25.3125 | 8.5625 | 24.75 | 635 | | X | C | 12 | SB 6325 | W/995 |
| | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3A95 | 25.3125 | 8.5625 | 24.75 | 610 | | X | C | 12 | SB 6325 | W/995 |
| | 24 | 12-P95-7 | 6.63 | 285 | 95 | 3A95 | 25.3125 | 8.5625 | 24.75 | 641 | | X | C | 12 | SB 6325 | W/995 |
| PE, PW 30.875 x 7.875 x 23.25 | 12 | 6-D85-13 | 5.94 | 510 | 85 | 1088 | 30.5 | 7.75 | 23.1875 | 538 | X | | A | 20 | SB 6325 | w/945 |
| | 12 | 6-H80-13 | 5.59 | 480 | 80 | 1088 | 30.5 | 7.75 | 23.1875 | 516 | X | | A | 20 | SB 6325 | w/945 |
| | 12 | 6-P95-13 | 6.63 | 570 | 95 | 1088 | 30.5 | 7.75 | 23.1875 | 543 | X | | A | 20 | SB 6325 | w/945 |
| PC, PE, PR, PW, TR, TW TWR 35.0625 x 6.625 x Open | 24 | 12-D85-5 | 3.96 | 170 | 85 | 3081 | 24.625 | 6.4375 | 23.1875 | 418 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-5 | 3.72 | 160 | 80 | 3081 | 24.625 | 6.4375 | 23.1875 | 401 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-5 | 4.42 | 190 | 95 | 3081 | 24.625 | 6.4375 | 23.1875 | 422 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3022 | 33.5625 | 6.4375 | 23.1875 | 574 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3022 | 33.5625 | 6.4375 | 23.1875 | 551 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-7 | 6.63 | 285 | 95 | 3022 | 33.5625 | 6.4375 | 23.1875 | 580 | X | | See Note B | | SB 6325 | w/945 |
| PC, PE, PR, PW, TR, TW TWR 31.75 x 13.125 x Open | 24 | 12-D85-11 | 9.89 | 425 | 85 | 3020 | 26.0625 | 12.75 | 23.25 | 885 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-11 | 9.31 | 400 | 80 | 3020 | 26.0625 | 12.75 | 23.25 | 850 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-11 | 11.06 | 475 | 95 | 3020 | 26.0625 | 12.75 | 23.25 | 894 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | See Note B | | SB 6325 | w/945 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | See Note B | | SB 6325 | w/945 |
| PC4500, PE4000, PE4500 PR4500, PW3520 31.125 x 13.1875 x 23.375 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | A | 20 | SB6325 | w/945 |
| | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | A | 20 | SB6325 | w/945 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | A | 20 | SB6325 | w/945 |
| PE4000, PE4500, PW3520 34.5 x 6.75 x 23.375 | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3022 | 33.5625 | 6.4375 | 23.1875 | 574 | X | | A | 20 | SB6325 | w/945 |
| | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3022 | 33.5625 | 6.4375 | 23.1875 | 551 | X | | A | 20 | SB6325 | w/945 |
| | 24 | 12-P95-7 | 6.63 | 285 | 95 | 3022 | 33.5625 | 6.4375 | 23.1875 | 580 | X | | A | 20 | SB6325 | w/945 |
| PW3510 31.125 x 7.9375 x 23.375 | 12 | 6-D85-13 | 5.94 | 510 | 85 | 1088 | 30.5 | 7.75 | 23.1875 | 538 | X | | A | 20 | SB6320 | w/919 |
| | 12 | 6-H80-13 | 5.59 | 480 | 80 | 1088 | 30.5 | 7.75 | 23.1875 | 516 | X | | A | 20 | SB6320 | w/919 |
| | 12 | 6-P95-13 | 6.63 | 570 | 95 | 1088 | 30.5 | 7.75 | 23.1875 | 543 | X | | A | 20 | SB6320 | w/919 |
| ST3000-20 25.5 x 7.25 x 24.125 | 24 | 12-D85-5 | 3.96 | 170 | 85 | 3081 | 24.625 | 6.4375 | 23.1875 | 418 | X | | A/B | 20 | SB6325 | |
| | 24 | 12-H80-5 | 3.72 | 160 | 80 | 3081 | 24.625 | 6.4375 | 23.1875 | 401 | X | | A/B | 20 | SB6325 | |
| | 24 | 12-P95-5 | 4.42 | 190 | 95 | 3081 | 24.625 | 6.4375 | 23.1875 | 422 | X | | A/B | 20 | SB6325 | |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

WALKIE, RIDER/WALKIE, TOW TRACTORS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. | |
|--|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|----------------------|------|-------------------|---------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Length Pos. (in.) | | | |
| SX3000-30 26.375 x 9.125 x 23.625 | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3042 | 25.25 | 8.5625 | 23.1875 | 567 | X | | A/B | 20 | SB6325 | |
| | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3042 | 25.25 | 8.5625 | 23.1875 | 544 | X | | A/B | 20 | SB6325 | |
| | 24 | 12-P95-7 | 6.63 | 285 | 95 | 3042 | 25.25 | 8.5625 | 23.1875 | 573 | X | | A/B | 20 | SB6325 | |
| TR3600, TR4500 31.125 x 13.1875 x 31.625 | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3008 | 30.5625 | 12.75 | 31.125 | 1455 | X | | A | 20 | SB6325 | |
| | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3008 | 30.5625 | 12.75 | 31.125 | 1440 | X | | A | 20 | SB6325 | |
| | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3008 | 30.5625 | 12.75 | 31.125 | 1470 | X | | A | 20 | SB6325 | |
| WE 2000, WE2300 WS 2000, WS2300 32.5 x 8.625 x 24.625 Min. Battery Wt. - 644 lbs. | 24 | 12-D85-7 | cm | 5.94 | 255 | 85 | 3706 | 32 | 8.5625 | 23.1875 | 680 | X | | A, B | 18 | SB 6325 |
| | 24 | 12-H80-7 | cm | 5.59 | 240 | 80 | 3706 | 32 | 8.5625 | 23.1875 | 653 | X | | A, B | 18 | SB 6325 |
| | 24 | 12-P95-7 | cm | 6.63 | 285 | 95 | 3706 | 32 | 8.5625 | 23.1875 | 687 | X | | A, B | 18 | SB 6325 |
| | 24 | 12-D85-7 | | 5.94 | 255 | 85 | 3654 | 27.5625 | 8.5625 | 22.5625 | 660 | | X | AB | 18 | SB 6325 |
| | 24 | 12-H80-7 | | 5.59 | 240 | 80 | 3654 | 27.5625 | 8.5625 | 22.5625 | 634 | | X | AB | 18 | SB 6325 |
| | 24 | 12-P95-7 | | 6.63 | 285 | 95 | 3654 | 27.5625 | 8.5625 | 22.5625 | 667 | | X | AB | 18 | SB 6325 |
| WP2030, WP2035, WP2330 WP2335 25.8125 x 7.9375 x 26 | 24 | (4) 8GGC2 | pm | 3.60 | 155 | | 3801 | 25.5 | 7.5 | 24.5 | 340 | X | | A | 26 | SB 6325 |
| | 24 | 12-D85-5 | | 3.96 | 170 | 85 | 3996 | 25.5 | 7.5 | 23.1875 | 466 | X | | A | 20 | SB 6325 |
| | 24 | 12-D85-5 | | 3.96 | 170 | 85 | 3081 | 24.625 | 6.4375 | 23.1875 | 418 | X | | A | 20 | SB 6325 |
| | 24 | 12-H80-5 | | 3.72 | 160 | 80 | 3996 | 25.5 | 7.5 | 23.1875 | 447 | X | | A | 20 | SB 6325 |
| | 24 | 12-H80-5 | | 3.72 | 160 | 80 | 3081 | 24.625 | 6.4375 | 23.1875 | 401 | X | | A | 20 | SB 6325 |
| | 24 | 12-P95-5 | | 4.42 | 190 | 95 | 3996 | 25.5 | 7.5 | 23.1875 | 471 | X | | A | 20 | SB 6325 |
| WP2040, WP2045, WP2340 WP2345, WP3040, WP3045 25.8125 x 9.125 x 26 | 24 | (4) 8GGC2 | pm | 3.60 | 155 | | 3800 | 25.5 | 8.5625 | 24.5 | 340 | X | | A | 26 | SB 6325 |
| | 24 | 12-D85-7 | | 5.94 | 255 | 85 | 3042 | 25.25 | 8.5625 | 23.1875 | 567 | X | | A | 20 | SB 6325 |
| | 24 | 12-H80-7 | | 5.59 | 240 | 80 | 3042 | 25.25 | 8.5625 | 23.1875 | 544 | X | | A | 20 | SB 6325 |
| | 24 | 12-P95-7 | | 6.63 | 285 | 95 | 3042 | 25.25 | 8.5625 | 23.1875 | 573 | X | | A | 20 | SB 6325 |

* Note: Consult Factory for Special Battery and Pricing For Weight Variance.

Note A: GPW requires cable cut out in cover.

Note B: W, WA, WB, WR, A-18"; TW, TWR, TR without SCR Control, B-12"; TW, TWR, TR with SCR Control, A-12"; PW, PE, PC, PR, A-20".

cm - Charge-Mate includes on-board charger

pm - Powr-Mate includes on-board charger.

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STOCK PICKERS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| 15SP48, 30SP42, 30SP48 | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3025 | 35.0625 | 13.1875 | 30.5 | 1647 | | X | A | 21 | SB 6322 |
| SP3010-30, SP3015-30 | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3036 | 35.0625 | 12.875 | 30.5 | 1651 | | X | A | 21 | SB 6322 |
| SP3020-30, SP3040-30 | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3036 | 35.0625 | 12.875 | 30.5 | 1634 | | X | A | 21 | SB 6322 |
| SP3210-30, SP3220-30 | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3036 | 35.0625 | 12.875 | 30.5 | 1668 | | X | A | 21 | SB 6322 |
| SP3250H-30, SP3410-30 | | | | | | | | | | | | | | | |
| SP3420-30, SP3450H-30 | | | | | | | | | | | | | | | |
| SP3510-30, SP3520-30 | | | | | | | | | | | | | | | |
| SP3550H-30, SP3570F | | | | | | | | | | | | | | | |
| SP3580F | | | | | | | | | | | | | | | |
| 36.25 x 14.25 x 31 | | | | | | | | | | | | | | | |
| 30SP36 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3082 | 30.5625 | 12.75 | 22.625 | 1025 | | X | A | 18 | SB 6325 w/945 |
| 31.75 x 13.125 x 23.25 | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3082 | 30.5625 | 12.75 | 22.625 | 984 | | X | A | 18 | SB 6325 w/945 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3082 | 30.5625 | 12.75 | 22.625 | 1035 | | X | A | 18 | SB 6325 w/945 |
| SP3205-30 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3082 | 30.5625 | 12.75 | 22.625 | 1025 | | X | A | 21 | SB 6322 |
| 31.75 x 13.125 x 23.25 | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3082 | 30.5625 | 12.75 | 22.625 | 984 | | X | A | 21 | SB 6322 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3082 | 30.5625 | 12.75 | 22.625 | 1035 | | X | A | 21 | SB 6322 |
| SP3405-30, SP3505-30 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3019 | 30.5625 | 12.75 | 23.25 | 1049 | X | | A | 21 | SB 6325 |
| 31.75 x 13.125 x 23.25 | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3019 | 30.5625 | 12.75 | 23.25 | 1007 | X | | A | 21 | SB 6325 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3019 | 30.5625 | 12.75 | 23.25 | 1059 | X | | A | 21 | SB 6325 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

SLIP SHEET RIDER

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| SSR 36.375 x 11.75 x Open | 24 | 12-D160-9 | 14.90 | 640 | 160 | 3007 | 35.062 | 10.937 | 31.125 | 1417 | X | | A | 12 | SB 6322 |
| | 24 | 12-D125-11 | 14.55 | 625 | 125 | 3013 | 31.875 | 10.8125 | 31.125 | 1247 | X | | A | 12 | SB 6322 |
| | 24 | 12-H120-11 | 13.97 | 600 | 120 | 3013 | 31.875 | 10.8125 | 31.125 | 1235 | X | | A | 12 | SB 6322 |
| | 24 | 12-P140-11 | 16.30 | 700 | 140 | 3013 | 31.875 | 10.8125 | 31.125 | 1259 | X | | A | 12 | SB 6322 |
| | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3179 | 35.5625 | 11.5625 | 31.125 | 1475 | X | | A | 12 | SB 6322 |
| | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3179 | 35.5625 | 11.5625 | 31.125 | 1460 | X | | A | 12 | SB 6322 |
| | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3179 | 35.5625 | 11.5625 | 31.125 | 1490 | X | | A | 12 | SB 6322 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

REACH, STRADDLE TRUCKS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|-----------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|---------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| RM6025, RMD6025 38.4375 x 16.25 x 31 Compartment "C" | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | A | 9 | SB6320 |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | A | 9 | SB6320 |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | A | 9 | SB6320 |
| RM6025, RMD6025 38.75 x 18 x 31 Compartment "D" | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | A | 9 | SB6320 |
| | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | A | 9 | SB6320 |
| | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | A | 9 | SB6320 |
| RM6025, RMD6025 38.6875 x 20.75 x 31 Compartment "E" | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | A | 9 | SB 6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | A | 9 | SB 6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | A | 9 | SB 6320 |
| 25RR, 30RS, 35RR, 40RS RR-3000-35, RS-3000-40 RS3510-40, RS3520-40 38.375 x 12.1875 x 31 | 24 | 12-D160-9 | 14.90 | 640 | 160 | 3511 | 35.0625 | 10.9375 | 30.5 | 1309 | | X | A | 9 | SB 6322 |
| | 24 | 12-D125-11 | 14.55 | 625 | 125 | 3014 | 31.875 | 10.8125 | 30.5 | 1244 | | X | A | 9 | SB 6322 |
| | 24 | 12-H120-11 | 13.97 | 600 | 120 | 3014 | 31.875 | 10.8125 | 30.5 | 1232 | | X | A | 9 | SB 6322 |
| | 24 | 12-P140-11 | 16.30 | 700 | 140 | 3014 | 31.875 | 10.8125 | 30.5 | 1256 | | X | A | 9 | SB 6322 |
| | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3176 | 35.5625 | 11.5625 | 30.5 | 1457 | | X | A | 9 | SB 6322 |
| | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3176 | 35.5625 | 11.5625 | 30.5 | 1442 | | X | A | 9 | SB 6322 |
| | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3176 | 35.5625 | 11.5625 | 30.5 | 1472 | | X | A | 9 | SB 6322 |
| | 36 | 18-D125-9 | 17.46 | 500 | 125 | 6063 | 37.6875 | 10.9375 | 30.5 | 1495 | | X | A | 9 | SB 6322 |
| | 36 | 18-H120-9 | 16.76 | 480 | 120 | 6063 | 37.6875 | 10.9375 | 30.5 | 1480 | | X | A | 9 | SB 6322 |
| 36 | 18-P140-9 | 19.56 | 560 | 140 | 6063 | 37.6875 | 10.9375 | 30.5 | 1510 | | X | A | 9 | SB 6322 | |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH, STRADDLE TRUCKS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| 25RR, 30RS, 35RR, 40RS | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3025 | 35.0625 | 13.1875 | 30.5 | 1647 | | X | A | 9 | SB 6322 |
| RR-3000-35, RR-3000-40 | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3093 | 30.5625 | 12.75 | 30.5 | 1444 | | X | A | 9 | SB 6322 |
| RS-3000-40, RS3510-40 | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3093 | 30.5625 | 12.75 | 30.5 | 1430 | | X | A | 9 | SB 6322 |
| 38.375 x 14.25 x 31 | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3093 | 30.5625 | 12.75 | 30.5 | 1458 | | X | A | 9 | SB 6322 |
| | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3036 | 35.0625 | 12.875 | 30.5 | 1651 | | X | A | 9 | SB 6322 |
| | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3036 | 35.0625 | 12.875 | 30.5 | 1634 | | X | A | 9 | SB 6322 |
| | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3036 | 35.0625 | 12.875 | 30.5 | 1668 | | X | A | 9 | SB 6322 |
| | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | | X | A | 9 | SB 6322 |
| | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | | X | A | 9 | SB 6322 |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | | X | A | 9 | SB 6322 |
| 24RR, 25RD, 30RD, 30RS | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | A | 9 | SB 6320 |
| 35RD, 35RR, 40RS, 45RR | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | A | 9 | SB 6320 |
| 50RS, RD 3000-30 | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | A | 9 | SB 6320 |
| RS3520-40 | | | | | | | | | | | | | | | |
| 38.375 x 14.25 x 31 | | | | | | | | | | | | | | | |
| 25RR, 30RS, 35RR, 40RS | 24 | 12-D160-13 | 22.35 | 960 | 160 | 3049 | 35.25 | 15.5625 | 30.5625 | 1985 | | X | A | 9 | SB 6322 |
| RR-3000-40, RR3000-35 | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | | X | A | 9 | SB 6322 |
| RS-3000-40, RS3510-40 | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | | X | A | 9 | SB 6322 |
| 38.375 x 16.25 x 31 | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | | X | A | 9 | SB 6322 |
| | 24 | 12-D125-19 | 26.19 | 1125 | 125 | 3134 | 38.1875 | 15 | 30.5625 | 2126 | | X | A | 9 | SB 6322 |
| | 24 | 12-H120-19 | 25.14 | 1080 | 120 | 3134 | 38.1875 | 15 | 30.5625 | 2105 | | X | A | 9 | SB 6322 |
| | 24 | 12-P140-19 | 29.33 | 1260 | 140 | 3134 | 38.1875 | 15 | 30.5625 | 2147 | | X | A | 9 | SB 6322 |
| 25RD, 25RR, 30RD, 30RS | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | A | 9 | SB 6320 |
| 35RD, 35RR, 40RS, 45RR | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | A | 9 | SB 6320 |
| 50RS, RD-3000-30 | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | A | 9 | SB 6320 |
| RR-3000-45, RS-3000-40 | | | | | | | | | | | | | | | |
| RS3520-40 | | | | | | | | | | | | | | | |
| 38.375 x 16.25 x 31 | | | | | | | | | | | | | | | |
| 30RD, 45RR, RD-3000-30 | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | A | 9 | SB 6320 |
| RR-3000-45 | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | A | 9 | SB 6320 |
| 38.5625 x 18 x 31 | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | A | 9 | SB 6320 |
| 38.5625 x 20.75 x 31 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | A | 9 | SB 6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | A | 9 | SB 6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | A | 9 | SB 6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH, STRADDLE TRUCKS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. | |
|--|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|----------------------|----|-------------------|--|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Length Pos. (in.) | | | |
| RR5010-35 38.375 x 12.1875 x 31 Min. Battery Wt. - 1300 lbs. | 24 | 12-D160-9 | 14.90 | 640 | 160 | 3511 | 35.0625 | 10.9375 | 30.5 | 1309 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-D125-13 | 17.46 | 750 | 125 | 3176 | 35.5625 | 11.5625 | 30.5 | 1457 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-H120-13 | 16.76 | 720 | 120 | 3176 | 35.5625 | 11.5625 | 30.5 | 1442 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-P140-13 | 19.56 | 840 | 140 | 3176 | 35.5625 | 11.5625 | 30.5 | 1472 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3115 | 38.0625 | 11.875 | 30.5 | 1677 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3115 | 38.0625 | 11.875 | 30.5 | 1660 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3115 | 38.0625 | 11.875 | 30.5 | 1694 | X | | D-Rear | 18 | SB 6322 | |
| RR5010-35, RR5010-40 38.375 x 14.25 x 31 Min. Battery Wt. - 1600 lbs. | 24 | 12-D160-11 | 18.62 | 800 | 160 | 3025 | 35.0625 | 13.1875 | 30.5 | 1647 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3036 | 35.0625 | 12.875 | 30.5 | 1651 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3036 | 35.0625 | 12.875 | 30.5 | 1634 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3036 | 35.0625 | 12.875 | 30.5 | 1668 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | X | | D-Rear | 18 | SB 6322 | |
| RR5010-35, RR5010-40 38.375 x 16.25 x 31 Min. Battery Wt. - 1880 lbs. | 24 | 12-D160-13 | 22.35 | 960 | 160 | 3049 | 35.25 | 15.5625 | 30.5625 | 1985 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-D125-17 | 23.28 | 1000 | 125 | 3127 | 38.1875 | 13.5 | 30.5625 | 1944 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-H120-17 | 22.35 | 960 | 120 | 3127 | 38.1875 | 13.5 | 30.5625 | 1925 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-P140-17 | 26.07 | 1120 | 140 | 3127 | 38.1875 | 13.5 | 30.5625 | 1963 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-D125-19 | 26.19 | 1125 | 125 | 3134 | 38.1875 | 15 | 30.5625 | 2126 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-H120-19 | 25.14 | 1080 | 120 | 3134 | 38.1875 | 15 | 30.5625 | 2105 | X | | D-Rear | 18 | SB 6322 | |
| | 24 | 12-P140-19 | 29.33 | 1260 | 140 | 3134 | 38.1875 | 15 | 30.5625 | 2147 | X | | D-Rear | 18 | SB 6322 | |
| RR5020-35 38.375 x 12.1875 x 31 Min. Battery Wt. - 1300 lbs. | 36 | 18-D125-9 | 17.46 | 500 | 125 | 6063 | 37.6875 | 10.9375 | 30.5 | 1495 | X | | D-Rear | 18 | SB 6320 | |
| | 36 | 18-H120-9 | 16.76 | 480 | 120 | 6063 | 37.6875 | 10.9375 | 30.5 | 1480 | X | | D-Rear | 18 | SB 6320 | |
| | 36 | 18-P140-9 | 19.56 | 560 | 140 | 6063 | 37.6875 | 10.9375 | 30.5 | 1510 | X | | D-Rear | 18 | SB 6320 | |
| RR5020-35, RD5020-30 38.375 x 14.25 x 31 Min. Battery Wt. - 1600 lbs. | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | X | | D-Rear | 18 | SB 6320 | |
| | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | X | | D-Rear | 18 | SB 6320 | |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | X | | D-Rear | 18 | SB 6320 | |
| RR5020-35, RD5020-30 RD5060S-30, RD5080S-30 RR5020-45, RR5060S-45 RR5080S-45 38.375 x 16.25 x 31 Min. Battery Wt. - 2000 lbs. | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | X | | D-Rear | 18 | SB 6320 | |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | X | | D-Rear | 18 | SB 6320 | |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | X | | D-Rear | 18 | SB 6320 | |
| | | | | | | | | | | | | | | | | |
| | | | | | | | | | | | | | | | | |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH, STRADDLE TRUCKS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. |
|---|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|----------------------|----|-------------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Length Pos. (in.) | | |
| RR5020-45, RD5020-30 | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | D-Rear | 18 | SB 6320 |
| 38.6875 x 18 x 31 | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | D-Rear | 18 | SB 6320 |
| Min. Battery Wt. - 2280 lbs. | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | D-Rear | 18 | SB 6320 |
| RR5020-45, RD5020-30 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | D-Rear | 21 | SB 6320 |
| RD5060S-30, RD5080S-30 | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | D-Rear | 21 | SB 6320 |
| RR5060S-45, RR5080S-45 | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | D-Rear | 21 | SB 6320 |
| 38.6875 x 20.75 x 31 | | | | | | | | | | | | | | | |
| Min. Battery Wt. - 2600 lbs. | | | | | | | | | | | | | | | |
| RD5795S, RR5725-45 | 24 | 12-D125-19 | 26.19 | 1125 | 125 | 3953 | 38.1875 | 15.75 | 30.5625 | 2146 | | X | A | 11 | SB6320 |
| RR5795S | 24 | 12-H120-19 | 25.14 | 1080 | 120 | 3953 | 38.1875 | 15.75 | 30.5625 | 2125 | | X | A | 11 | SB6320 |
| 38.6875 x 16.25 x 31 | 24 | 12-P140-19 | 29.33 | 1260 | 140 | 3953 | 38.1875 | 15.75 | 30.5625 | 2167 | | X | A | 11 | SB6320 |
| Compartment "C" | | | | | | | | | | | | | | | |
| RD5795S, RR5725-45 | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | A | 11 | SB6320 |
| RR5795S | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | A | 11 | SB6320 |
| 38.6875 x 18 x 31 | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | A | 11 | SB6320 |
| Compartment "D" | | | | | | | | | | | | | | | |
| RD5795S, RR5725-45 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | A | 11 | SB6320 |
| RR5795S | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | A | 11 | SB6320 |
| 38.6875 x 20.75 x 31 | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | A | 11 | SB6320 |
| Compartment "E" | | | | | | | | | | | | | | | |
| RM6095S, RM6025 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | A | 9 | SB6320 |
| RMD6095S | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | A | 9 | SB6320 |
| 38.6875 x 20.75 x 31 | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | A | 9 | SB6320 |
| Compartment "E" | | | | | | | | | | | | | | | |
| RMD6025 | | | | | | | | | | | | | | | |
| RM6095S, RMD6095S | 36 | 18-D125-19 | 39.29 | 1125 | 125 | 6089 | 38.1875 | 22.3125 | 30.5625 | 3106 | | X | A | 9 | SB6320 |
| 38.6875 x 22.75 x 31 | 36 | 18-H120-19 | 37.71 | 1080 | 120 | 6089 | 38.1875 | 22.3125 | 30.5625 | 3075 | | X | A | 9 | SB6320 |
| Compartment "F" | 36 | 18-P140-19 | 44.00 | 1260 | 140 | 6089 | 38.1875 | 22.3125 | 30.5625 | 3137 | | X | A | 9 | SB6320 |
| RR5715-35, RR5715-40 | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3A03 | 37.875 | 12.9375 | 30.5 | 1600 | | X | A | 11 | SB6320 |
| 38.375 x 14.25 x 31 | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3A03 | 37.875 | 12.9375 | 30.5 | 1584 | | X | A | 11 | SB6320 |
| Compartment "B" | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3A03 | 37.875 | 12.9375 | 30.5 | 1616 | | X | A | 11 | SB6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

REACH, STRADDLE TRUCKS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| RR5725-35 | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | A | 11 | SB6320 |
| 38.375 x 14.25 x 31 | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | A | 11 | SB6320 |
| Compartment "B" | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | A | 11 | SB6320 |
| RR5715-35, RR5715-40 | 24 | 12-D125-15 | 20.37 | 875 | 125 | 3A01 | 35.875 | 15.75 | 30.5625 | 1800 | | X | A | 11 | SB6320 |
| 38.375 x 16.25 x 31 | 24 | 12-H120-15 | 19.56 | 840 | 120 | 3A01 | 35.875 | 15.75 | 30.5625 | 1782 | | X | A | 11 | SB6320 |
| Compartment "C" | 24 | 12-P140-15 | 22.81 | 980 | 140 | 3A01 | 35.875 | 15.75 | 30.5625 | 1818 | | X | A | 11 | SB6320 |
| RR5725-35 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | A | 11 | SB6320 |
| 38.375 x 16.25 x 31 | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | A | 11 | SB6320 |
| Compartment "C" | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | A | 11 | SB6320 |
| SH5520-40, SHR5520-25 | 24 | 12-D85-7 | 5.94 | 255 | 85 | 3079 | 33.5625 | 6.4375 | 22.5625 | 567 | | X | B | 20 | SB6325 |
| SHR5520-30 | 24 | 12-H80-7 | 5.59 | 240 | 80 | 3079 | 33.5625 | 6.4375 | 22.5625 | 544 | | X | B | 20 | SB6325 |
| 34.375 x 6.625 x 24.8125 | 24 | 12-P95-7 | 6.63 | 285 | 95 | 3079 | 33.5625 | 6.4375 | 22.5625 | 573 | | X | B | 20 | SB6325 |
| SH5540-40, SHR5540-35 | 24 | 12-D85-13 | 11.87 | 510 | 85 | 3082 | 30.5625 | 12.75 | 22.625 | 1025 | | X | B | 20 | SB6325 |
| 31.125 x 13.125 x 24.8125 | 24 | 12-H80-13 | 11.17 | 480 | 80 | 3082 | 30.5625 | 12.75 | 22.625 | 984 | | X | B | 20 | SB6325 |
| | 24 | 12-P95-13 | 13.27 | 570 | 95 | 3082 | 30.5625 | 12.75 | 22.625 | 1035 | | X | B | 20 | SB6325 |
| SR5000 (46" COMPART) | 48 | 24-D125-15 | 40.74 | 875 | 125 | 7735 | 46.6875 | 19.3125 | 30.5625 | 3266 | | X | - | | SB6321 |
| 46.9375 x 19.625 x 30.5625 | 48 | 24-H120-15 | 39.11 | 840 | 120 | 7735 | 46.6875 | 19.3125 | 30.5625 | 3233 | | X | - | | SB6321 |
| (Actual Battery Dimensions) | 48 | 24-P140-15 | 45.63 | 980 | 140 | 7735 | 46.6875 | 19.3125 | 30.5625 | 3299 | | X | - | | SB6321 |
| SR5000 (48" COMPART) | 48 | 24-D125-15 | 40.74 | 875 | 125 | 7533 | 48 | 19.3125 | 30.5625 | 3308 | | X | - | | SB6321 |
| 48.1875 x 19.625 x 30.5625 | 48 | 24-H120-15 | 39.11 | 840 | 120 | 7533 | 48 | 19.3125 | 30.5625 | 3275 | | X | - | | SB6321 |
| (Actual Battery Dimensions) | 48 | 24-P140-15 | 45.63 | 980 | 140 | 7533 | 48 | 19.3125 | 30.5625 | 3341 | | X | - | | SB6321 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

STAND-UP RIDERS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| RC25 | 36 | 18-D125-9 | 17.46 | 500 | 125 | 6063 | 37.6875 | 10.9375 | 30.5 | 1495 | | X | A | 9 | SB 6320 |
| 38.5625 x 11.4375 x 31 | 36 | 18-H120-9 | 16.76 | 480 | 120 | 6063 | 37.6875 | 10.9375 | 30.5 | 1480 | | X | A | 9 | SB 6320 |
| | 36 | 18-P140-9 | 19.56 | 560 | 140 | 6063 | 37.6875 | 10.9375 | 30.5 | 1510 | | X | A | 9 | SB 6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

STAND-UP RIDERS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|--|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| RC25, RC30, RC3020-30 38.5625 x 13.6875 x 31 | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | A | 9 | SB 6320 |
| | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | A | 9 | SB 6320 |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | A | 9 | SB 6320 |
| RC30, RC3020-30 38.5625 x 15.875 x 31 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | A | 9 | SB 6320 |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | A | 9 | SB 6320 |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | A | 9 | SB 6320 |
| RC30, RC3020-35, RC35 38.5625 x 18.375 x 31 | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | A | 9 | SB 6320 |
| | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | A | 9 | SB 6320 |
| | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | A | 9 | SB 6320 |
| RC3020-40, RC40 38.5625 x 20.75 x 31 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | A | 9 | SB 6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | A | 9 | SB 6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | A | 9 | SB 6320 |
| RC5510-30, RC5515-30 38.5625 x 13.625 x 31 | 36 | 18-D125-11 | 21.83 | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | A | 9 | SB6320 |
| | 36 | 18-H120-11 | 20.95 | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | A | 9 | SB6320 |
| | 36 | 18-P140-11 | 24.44 | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | A | 9 | SB6320 |
| RC5520-30, RC5525-30 38.5625 x 15.875 x 31 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | A | 9 | SB6320 |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | A | 9 | SB6320 |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | A | 9 | SB6320 |
| RC5530-30, RC5530-35 RC5535-30, RC5535-35 38.5625 x 18.1875 x 31 | 36 | 18-D125-15 | 30.56 | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | A | 9 | SB6320 |
| | 36 | 18-H120-15 | 29.33 | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | A | 9 | SB6320 |
| | 36 | 18-P140-15 | 34.22 | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | A | 9 | SB6320 |
| RC5540-40, RC5540-45 38.5625 x 20.5 x 31 | 36 | 18-D125-17 | 34.92 | 1000 | 125 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2834 | | X | A | 9 | SB6320 |
| | 36 | 18-H120-17 | 33.52 | 960 | 120 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2806 | | X | A | 9 | SB6320 |
| | 36 | 18-P140-17 | 39.11 | 1120 | 140 | 6069 | 38.1875 | 20.0625 | 30.5625 | 2862 | | X | A | 9 | SB6320 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

THREE WHEEL SIT-DOWN RIDERS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|--|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| SC25 38.625 x 15.875 x 23.125 | 36 | 18-D85-13 | 17.81 | 510 | 85 | 6062 | 37.6875 | 15.4375 | 22.625 | 1507 | | X | A | 9 | SB 6320 |
| | 36 | 18-H80-13 | 16.76 | 480 | 80 | 6062 | 37.6875 | 15.4375 | 22.625 | 1447 | | X | A | 9 | SB 6320 |
| | 36 | 18-P95-13 | 19.90 | 570 | 95 | 6062 | 37.6875 | 15.4375 | 22.625 | 1522 | | X | A | 9 | SB 6320 |
| SC25 38.625 x 18.375 x 23.125 | 36 | 18-D85-15 | 20.78 | 595 | 85 | 6002 | 38.1875 | 17.8125 | 22.6875 | 1780 | | X | A | 9 | SB 6320 |
| | 36 | 18-H80-15 | 19.56 | 560 | 80 | 6002 | 38.1875 | 17.8125 | 22.6875 | 1709 | | X | A | 9 | SB 6320 |
| | 36 | 18-P95-15 | 23.22 | 665 | 95 | 6002 | 38.1875 | 17.8125 | 22.6875 | 1798 | | X | A | 9 | SB 6320 |
| SC30 38.5625 x 20.625 x 23.125 | 36 | 18-D85-17 | 23.75 | 680 | 85 | 6015 | 38.1875 | 20.0625 | 22.6875 | 2045 | | X | A | 9 | SB 6320 |
| | 36 | 18-H80-17 | 22.35 | 640 | 80 | 6015 | 38.1875 | 20.0625 | 22.6875 | 1963 | | X | A | 9 | SB 6320 |
| | 36 | 18-P95-17 | 26.54 | 760 | 95 | 6015 | 38.1875 | 20.0625 | 22.6875 | 2065 | | X | A | 9 | SB 6320 |
| SC30, SC35 38.5625 x 22.8125 x 23.125 | 36 | 18-D85-19 | 26.71 | 765 | 85 | 6041 | 38.1875 | 22.3125 | 22.6875 | 2242 | | X | A | 9 | SB 6320 |
| | 36 | 18-H80-19 | 25.14 | 720 | 80 | 6041 | 38.1875 | 22.3125 | 22.6875 | 2152 | | X | A | 9 | SB 6320 |
| | 36 | 18-P95-19 | 29.86 | 855 | 95 | 6041 | 38.1875 | 22.3125 | 22.6875 | 2264 | | X | A | 9 | SB 6320 |
| SC4010-30, SC4510-30 38.8125 x 16.0625 x 22.8125 | 36 | 18-D85-13 | 17.81 | 510 | 85 | 6062 | 37.6875 | 15.4375 | 22.625 | 1507 | | X | A | 9 | SB6320 |
| | 36 | 18-H80-13 | 16.76 | 480 | 80 | 6062 | 37.6875 | 15.4375 | 22.625 | 1447 | | X | A | 9 | SB6320 |
| | 36 | 18-P95-13 | 19.90 | 570 | 95 | 6062 | 37.6875 | 15.4375 | 22.625 | 1522 | | X | A | 9 | SB6320 |
| SC4020-30, SC4020-35 SC4520-30, SC4520-35 38.8125 x 20.5 x 22.8125 | 36 | 18-D85-17 | 23.75 | 680 | 85 | 6015 | 38.1875 | 20.0625 | 22.6875 | 2045 | | X | A | 9 | SB 6320 |
| | 36 | 18-H80-17 | 22.35 | 640 | 80 | 6015 | 38.1875 | 20.0625 | 22.6875 | 1963 | | X | A | 9 | SB 6320 |
| | 36 | 18-P95-17 | 26.54 | 760 | 95 | 6015 | 38.1875 | 20.0625 | 22.6875 | 2065 | | X | A | 9 | SB 6320 |
| SC4040-30, SC4040-35 SC4540-35, SC4540-40 38.8125 x 24.875 x 22.8125 | 36 | 18-D85-21 | 29.68 | 850 | 85 | 6010 | 38.1875 | 24.5625 | 22.6875 | 2466 | | X | A | 9 | SB 6320 |
| | 36 | 18-H80-21 | 27.94 | 800 | 80 | 6010 | 38.1875 | 24.5625 | 22.6875 | 2367 | | X | A | 9 | SB 6320 |
| | 36 | 18-P95-21 | 33.17 | 950 | 95 | 6010 | 38.1875 | 24.5625 | 22.6875 | 2491 | | X | A | 9 | SB 6320 |
| SC522X-30, SC522X-35 38.8125 x 20.875 x 22.8125 | 36 | 18-D85-17 | 23.75 | 680 | 85 | 6015 | 38.1875 | 20.0625 | 22.6875 | 2045 | | X | A | 9 | SB6320 |
| | 36 | 18-H80-17 | 22.35 | 640 | 80 | 6015 | 38.1875 | 20.0625 | 22.6875 | 1963 | | X | A | 9 | SB6320 |
| | 36 | 18-P95-17 | 26.54 | 760 | 95 | 6015 | 38.1875 | 20.0625 | 22.6875 | 2065 | | X | A | 9 | SB6320 |
| SC524X-35, SC524X-40 38.8125 x 25.125 x 22.8125 | 36 | 18-D85-21 | 29.68 | 850 | 85 | 6010 | 38.1875 | 24.5625 | 22.6875 | 2466 | | X | A | 9 | SB6320 |
| | 36 | 18-H80-21 | 27.94 | 800 | 80 | 6010 | 38.1875 | 24.5625 | 22.6875 | 2367 | | X | A | 9 | SB6320 |
| | 36 | 18-P95-21 | 33.17 | 950 | 95 | 6010 | 38.1875 | 24.5625 | 22.6875 | 2491 | | X | A | 9 | SB6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

THREE WHEEL SIT-DOWN RIDERS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|--|------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| SC521X-30 38.8125 x 16.6875 x 31 | 36 | 18-D125-13 | 26.19 | 750 | 125 | 6D44 | 38.25 | 16.0625 | 30.5625 | 2170 | | X | A | 9 | SB6320 |
| | 36 | 18-H120-13 | 25.14 | 720 | 120 | 6D44 | 38.25 | 16.0625 | 30.5625 | 2148 | | X | A | 9 | SB6320 |
| | 36 | 18-P140-13 | 29.33 | 840 | 140 | 6D44 | 38.25 | 16.0625 | 30.5625 | 2192 | | X | A | 9 | SB6320 |
| SC521X-30 38.8125 x 16.625 x 22.8125 | 48 | 24-D85-9 | 15.83 | 340 | 85 | 7885 | 38.3125 | 16.125 | 22.625 | 1471 | | X | A | 9 | SB6320 |
| | 48 | 24-H80-9 | 14.90 | 320 | 80 | 7885 | 38.3125 | 16.125 | 22.625 | 1412 | | X | A | 9 | SB6320 |
| | 48 | 24-P95-9 | 17.69 | 380 | 95 | 7885 | 38.3125 | 16.125 | 22.625 | 1486 | | X | A | 9 | SB6320 |
| SC522X-30, SC522X-35 38.8125 x 20.875 x 22.8125 | 48 | 24-D85-13 | 23.75 | 510 | 85 | 7071 | 38.125 | 20.4375 | 22.6875 | 2022 | | X | A | 9 | SB6320 |
| | 48 | 24-H80-13 | 22.35 | 480 | 80 | 7071 | 38.125 | 20.4375 | 22.6875 | 1941 | | X | A | 9 | SB6320 |
| | 48 | 24-P95-13 | 26.54 | 570 | 95 | 7071 | 38.125 | 20.4375 | 22.6875 | 2042 | | X | A | 9 | SB6320 |
| SC524X-35, SC524X-40 38.8125 x 25.125 x 22.8125 | 48 | 24-D85-15 | 27.70 | 595 | 85 | 7031 | 38.1875 | 23.5625 | 22.6875 | 2332 | | X | A | 9 | SB6320 |
| | 48 | 24-H80-15 | 26.07 | 560 | 80 | 7031 | 38.1875 | 23.5625 | 22.6875 | 2239 | | X | A | 9 | SB6320 |
| | 48 | 24-P95-15 | 30.96 | 665 | 95 | 7031 | 38.1875 | 23.5625 | 22.6875 | 2355 | | X | A | 9 | SB6320 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

FOUR WHEEL SIT-DOWN RIDERS

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|--|------|--------------|----------------|------|----------------|--------------|--------------------------|---------|----------|--------------------------|-------|----|--------------|-------|----------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| 40FC, 50FC Standard Compartment 38.6875 x 27.1875 x 23 | 36 | 18-D85-23 | 32.65 | 935 | 85 | 6009 | 38.1875 | 26.9375 | 22.6875 | 2703 | | X | A | 15 | SB 6320 |
| | 36 | 18-H80-23 | 30.73 | 880 | 80 | 6009 | 38.1875 | 26.9375 | 22.6875 | 2595 | | X | A | 15 | SB 6320 |
| | 36 | 18-P95-23 | 36.49 | 1045 | 95 | 6009 | 38.1875 | 26.9375 | 22.6875 | 2730 | | X | A | 15 | SB 6320 |
| | 48 | 24-D85-17 | 31.66 | 680 | 85 | 7002 | 38.1875 | 26.6875 | 22.6875 | 2695 | | X | A | 15 | SB 6320 |
| | 48 | 24-H80-17 | 29.80 | 640 | 80 | 7002 | 38.1875 | 26.6875 | 22.6875 | 2587 | | X | A | 15 | SB 6320 |
| | 48 | 24-P95-17 | 35.39 | 760 | 95 | 7002 | 38.1875 | 26.6875 | 22.6875 | 2722 | | X | A | 15 | SB 6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

FOUR WHEEL SIT-DOWN RIDERS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. |
|--|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|----------------------|----|-------------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Length Pos. (in.) | | |
| 40FC, 50FC, 55FC, 60FC Optional Compartment #1 38.6875 x 32.875 x 23 | 36 | 18-D85-25 | 35.62 | 1020 | 85 | 6030 | 38.1875 | 29.1875 | 22.6875 | 2924 | | X | A | 15 | SB 6320 |
| | 36 | 18-H80-25 | 33.52 | 960 | 80 | 6030 | 38.1875 | 29.1875 | 22.6875 | 2807 | | X | A | 15 | SB 6320 |
| | 36 | 18-P95-25 | 39.81 | 1140 | 95 | 6030 | 38.1875 | 29.1875 | 22.6875 | 2953 | | X | A | 15 | SB 6320 |
| | 36 | 18-D85-27 | 38.59 | 1105 | 85 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3144 | | X | A | 15 | SB 6320 |
| | 36 | 18-H80-27 | 36.32 | 1040 | 80 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3018 | | X | A | 15 | SB 6320 |
| | 36 | 18-P95-27 | 43.13 | 1235 | 95 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3175 | | X | A | 15 | SB 6320 |
| | 48 | 24-D85-19 | 35.62 | 765 | 85 | 7003 | 38.1875 | 29.6875 | 22.6875 | 2984 | | X | A | 15 | SB 6320 |
| | 48 | 24-H80-19 | 33.52 | 720 | 80 | 7003 | 38.1875 | 29.6875 | 22.6875 | 2865 | | X | A | 15 | SB 6320 |
| | 48 | 24-P95-19 | 39.81 | 855 | 95 | 7003 | 38.1875 | 29.6875 | 22.6875 | 3014 | | X | A | 15 | SB 6320 |
| | 48 | 24-D85-21 | 39.58 | 850 | 85 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3272 | | X | A | 15 | SB 6320 |
| | 48 | 24-H80-21 | 37.25 | 800 | 80 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3141 | | X | A | 15 | SB 6320 |
| | 48 | 24-P95-21 | 44.23 | 950 | 95 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3305 | | X | A | 15 | SB 6320 |
| 60FC, 50FC, 55FC Optional Compartment #2 38.6875 x 36.375 x 23 | 36 | 18-D85-29 | 41.55 | 1190 | 85 | 6021 | 38.1875 | 33.6875 | 22.6875 | 3394 | | X | A | 15 | SB 6320 |
| | 36 | 18-H80-29 | 39.11 | 1120 | 80 | 6021 | 38.1875 | 33.6875 | 22.6875 | 3258 | | X | A | 15 | SB 6320 |
| | 36 | 18-P95-29 | 46.44 | 1330 | 95 | 6021 | 38.1875 | 33.6875 | 22.6875 | 3428 | | X | A | 15 | SB 6320 |
| | 36 | 18-D85-31 | 44.52 | 1275 | 85 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3603 | | X | A | 15 | SB 6320 |
| | 36 | 18-H80-31 | 41.90 | 1200 | 80 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3459 | | X | A | 15 | SB 6320 |
| | 36 | 18-P95-31 | 49.76 | 1425 | 95 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3639 | | X | A | 15 | SB 6320 |
| | 48 | 24-D85-23 | 43.53 | 935 | 85 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3573 | | X | A | 15 | SB 6320 |
| | 48 | 24-H80-23 | 40.97 | 880 | 80 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3430 | | X | A | 15 | SB 6320 |
| | 48 | 24-P95-23 | 48.66 | 1045 | 95 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3609 | | X | A | 15 | SB 6320 |
| FP40, FP50 38.6875 x 32.9375 x 22.75 | 36 | 18-D85-27 | 38.59 | 1105 | 85 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3144 | | X | A | 15 | SB 6320 |
| | 36 | 18-H80-27 | 36.32 | 1040 | 80 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3018 | | X | A | 15 | SB 6320 |
| | 36 | 18-P95-27 | 43.13 | 1235 | 95 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3175 | | X | A | 15 | SB 6320 |
| | 48 | 24-D85-21 | 39.58 | 850 | 85 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3272 | | X | A | 15 | SB 6320 |
| | 48 | 24-H80-21 | 37.25 | 800 | 80 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3141 | | X | A | 15 | SB 6320 |
| | 48 | 24-P95-21 | 44.23 | 950 | 95 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3305 | | X | A | 15 | SB 6320 |
| FP60, FB40, FB50, FP55 Optional Compartment 38.6875 x 36.375 x 22.75 | 36 | 18-D85-31 | 44.52 | 1275 | 85 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3603 | | X | A | 15 | SB 6320 |
| | 36 | 18-H80-31 | 41.90 | 1200 | 80 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3459 | | X | A | 15 | SB 6320 |
| | 36 | 18-P95-31 | 49.76 | 1425 | 95 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3639 | | X | A | 15 | SB 6320 |
| | 48 | 24-D85-23 | 43.53 | 935 | 85 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3573 | | X | A | 15 | SB 6320 |
| | 48 | 24-H80-23 | 40.97 | 880 | 80 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3430 | | X | A | 15 | SB 6320 |
| | 48 | 24-P95-23 | 48.66 | 1045 | 95 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3609 | | X | A | 15 | SB 6320 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

FOUR WHEEL SIT-DOWN RIDERS (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| FC4010-40, FC4010-50 | 36 | 18-D85-23 | 32.65 | 935 | 85 | 6009 | 38.1875 | 26.9375 | 22.6875 | 2703 | | X | A | 18 | SB6320 |
| FC4510-40, FC4510-50 | 36 | 18-H80-23 | 30.73 | 880 | 80 | 6009 | 38.1875 | 26.9375 | 22.6875 | 2595 | | X | A | 18 | SB6320 |
| FC4515-40, FC4515-50 | 36 | 18-P95-23 | 36.49 | 1045 | 95 | 6009 | 38.1875 | 26.9375 | 22.6875 | 2730 | | X | A | 18 | SB6320 |
| 38.6875 x 27.25 x 22.75 | 48 | 24-D85-17 | 31.66 | 680 | 85 | 7002 | 38.1875 | 26.6875 | 22.6875 | 2695 | | X | A | 18 | SB6320 |
| | 48 | 24-H80-17 | 29.80 | 640 | 80 | 7002 | 38.1875 | 26.6875 | 22.6875 | 2587 | | X | A | 18 | SB6320 |
| | 48 | 24-P95-17 | 35.39 | 760 | 95 | 7002 | 38.1875 | 26.6875 | 22.6875 | 2722 | | X | A | 18 | SB6320 |
| FC4020-40, FC4020-50 | 36 | 18-D85-27 | 38.59 | 1105 | 85 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3144 | | X | A | 18 | SB6320 |
| FC4020-55, FC4020-60 | 36 | 18-H80-27 | 36.32 | 1040 | 80 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3018 | | X | A | 18 | SB6320 |
| FC4520-40, FC4520-50 | 36 | 18-P95-27 | 43.13 | 1235 | 95 | 6026 | 38.1875 | 31.4375 | 22.6875 | 3175 | | X | A | 18 | SB6320 |
| FC4520-55, FC4520-60 | 48 | 24-D85-21 | 39.58 | 850 | 85 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3272 | | X | A | 18 | SB6320 |
| FC4525-40, FC4525-50 | 48 | 24-H80-21 | 37.25 | 800 | 80 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3141 | | X | A | 18 | SB6320 |
| FC4525-55, FC4525-60 | 48 | 24-P95-21 | 44.23 | 950 | 95 | 7004 | 38.1875 | 32.6875 | 22.6875 | 3305 | | X | A | 18 | SB6320 |
| 38.6875 x 32.9375 x 22.75 | | | | | | | | | | | | | | | |
| FC4040-50, FC4040-55 | 36 | 18-D85-31 | 44.52 | 1275 | 85 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3603 | | X | A | 18 | SB6320 |
| FC4040-60, FC4540-50 | 36 | 18-H80-31 | 41.90 | 1200 | 80 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3459 | | X | A | 18 | SB6320 |
| FC4540-55, FC4540-60 | 36 | 18-P95-31 | 49.76 | 1425 | 95 | 6164 | 38.1875 | 35.9375 | 22.6875 | 3639 | | X | A | 18 | SB6320 |
| FC4545-50, FC4545-55 | 48 | 24-D85-23 | 43.53 | 935 | 85 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3573 | | X | A | 18 | SB6320 |
| FC4545-60 | 48 | 24-H80-23 | 40.97 | 880 | 80 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3430 | | X | A | 18 | SB6320 |
| 38.6875 x 36.375 x 22.75 | 48 | 24-P95-23 | 48.66 | 1045 | 95 | 7059 | 38.1875 | 35.6875 | 22.6875 | 3609 | | X | A | 18 | SB6320 |

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

TURRET SIDE LOADER, TURRET STOCKPICKER

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. |
|---|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | |
| TSP | 48 | 24-D125-17 | 46.56 | 1000 | 125 | 7024 | 38.1875 | 26.6875 | 30.5625 | 3770 | | X | A | 9 | SB 6320 W/996 |
| 38.75 x 27 x 31 | 48 | 24-H120-17 | 44.70 | 960 | 120 | 7024 | 38.1875 | 26.6875 | 30.5625 | 3732 | | X | A | 9 | SB 6320 W/996 |
| | 48 | 24-P140-17 | 52.15 | 1120 | 140 | 7024 | 38.1875 | 26.6875 | 30.5625 | 3808 | | X | A | 9 | SB 6320 W/996 |
| TSP | 48 | 24-D125-21 | 58.20 | 1250 | 125 | 7121 | 38.25 | 32.75 | 30.5625 | 4579 | | X | A | 9 | SB 6320 W/996 |
| 38.75 x 33 x 31 | 48 | 24-H120-21 | 55.87 | 1200 | 120 | 7121 | 38.25 | 32.75 | 30.5625 | 4533 | | X | A | 9 | SB 6320 W/996 |
| | 48 | 24-P140-21 | 65.18 | 1400 | 140 | 7121 | 38.25 | 32.75 | 30.5625 | 4625 | | X | A | 9 | SB 6320 W/996 |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

TURRET SIDE LOADER, TURRET STOCKPICKER (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity 6 Hr. Rate | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads Length | | Standard Conn. | |
|---|------|-----------------|------------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-----------------|-------|-------------------|-------|
| | | | KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | (in.) | | |
| TS, 30TSP, TSP 38.5625 x 13.625 x 31 See Note C | 72 | 18-D125-11 | 21.83 ea | 625 | 125 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1848 | | X | A | 9 | SB 6320 | W/996 |
| | 72 | 18-H120-11 | 20.95 ea | 600 | 120 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1830 | | X | A | 9 | SB 6320 | W/996 |
| | 72 | 18-P140-11 | 24.44 ea | 700 | 140 | 6016 | 37.8125 | 13.3125 | 30.5625 | 1866 | | X | A | 9 | SB 6320 | W/996 |
| TS, 30TSP, TSP 38.5625 x 16.25 x 31 See Note C | 72 | 18-D125-13 | 26.19 ea | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | A | 9 | SB 6320 | W/996 |
| | 72 | 18-H120-13 | 25.14 ea | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | A | 9 | SB 6320 | W/996 |
| | 72 | 18-P140-13 | 29.33 ea | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | A | 9 | SB 6320 | W/996 |
| TS, 30TSP, 40TS, TSP 38.6875 x 18 x 31 See Note C | 72 | 18-D125-15 | 30.56 ea | 875 | 125 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2486 | | X | A | 9 | SB 6320 | W/996 |
| | 72 | 18-H120-15 | 29.33 ea | 840 | 120 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2461 | | X | A | 9 | SB 6320 | W/996 |
| | 72 | 18-P140-15 | 34.22 ea | 980 | 140 | 6045 | 38.1875 | 17.8125 | 30.5625 | 2511 | | X | A | 9 | SB 6320 | W/996 |
| 40TS 38.375 x 15.875 x 31 Compartment "C" See Note C | 72 | 18-D125-13 | 26.19 ea | 750 | 125 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2168 | | X | A | 9 | SB6320 | W/996 |
| | 72 | 18-H120-13 | 25.14 ea | 720 | 120 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2146 | | X | A | 9 | SB6320 | W/996 |
| | 72 | 18-P140-13 | 29.33 ea | 840 | 140 | 6005 | 37.8125 | 15.5625 | 30.5625 | 2190 | | X | A | 9 | SB6320 | W/996 |
| TSP6000 44.625 x 24.9375 x 31.25 | 48 | 24-D125-15 | 40.74 | 875 | 125 | 7403 | 44 | 23.5625 | 30.5625 | 3369 | | X | A | 15 | SB 6321 | |
| | 48 | 24-H120-15 | 39.11 | 840 | 120 | 7403 | 44 | 23.5625 | 30.5625 | 3335 | | X | A | 15 | SB 6321 | |
| | 48 | 24-P140-15 | 45.63 | 980 | 140 | 7403 | 44 | 23.5625 | 30.5625 | 3403 | | X | A | 15 | SB 6321 | |
| TSP6000 44.625 x 28.3125 x 31.25 | 48 | 24-D125-17 | 46.56 | 1000 | 125 | 7615 | 44 | 26.6875 | 30.5625 | 3848 | | X | A | 15 | SB 6321 | |
| | 48 | 24-H120-17 | 44.70 | 960 | 120 | 7615 | 44 | 26.6875 | 30.5625 | 3810 | | X | A | 15 | SB 6321 | |
| | 48 | 24-P140-17 | 52.15 | 1120 | 140 | 7615 | 44 | 26.6875 | 30.5625 | 3886 | | X | A | 15 | SB 6321 | |
| | 48 | 24-D125-19 | 52.38 | 1125 | 125 | 7563 | 44.1875 | 25.5625 | 30.5625 | 4131 | | X | A | 15 | SB 6321 | |
| | 48 | 24-H120-19 | 50.28 | 1080 | 120 | 7563 | 44.1875 | 25.5625 | 30.5625 | 4090 | | X | A | 15 | SB 6321 | |
| | 48 | 24-P140-19 | 58.67 | 1260 | 140 | 7563 | 44.1875 | 25.5625 | 30.5625 | 4172 | | X | A | 15 | SB 6321 | |
| TSP6000 44.625 x 33.9375 x 31.25 | 48 | 24-D125-21 | 58.20 | 1250 | 125 | 7616 | 44 | 32.6875 | 30.5625 | 4676 | | X | A | 15 | SB 6321 | |
| | 48 | 24-H120-21 | 55.87 | 1200 | 120 | 7616 | 44 | 32.6875 | 30.5625 | 4629 | | X | A | 15 | SB 6321 | |
| | 48 | 24-P140-21 | 65.18 | 1400 | 140 | 7616 | 44 | 32.6875 | 30.5625 | 4723 | | X | A | 15 | SB 6321 | |
| | 48 | 24-D125-23 | 64.02 | 1375 | 125 | 7613 | 44.5625 | 32.0625 | 30.625 | 5117 | | X | A | 15 | SB 6321 | |
| | 48 | 24-H120-23 | 61.46 | 1320 | 120 | 7613 | 44.5625 | 32.0625 | 30.625 | 5066 | | X | A | 15 | SB 6321 | |
| | 48 | 24-P140-23 | 71.70 | 1540 | 140 | 7613 | 44.5625 | 32.0625 | 30.625 | 5168 | | X | A | 15 | SB 6321 | |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are ±1/16". Battery weights may vary ±5%. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

TURRET SIDE LOADER, TURRET STOCKPICKER (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard | |
|---|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|----------------------|-------|----------|-------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Length Pos. (in.) | Conn. | | |
| TSP6000-30TF | 48 | 24-D125-15 | 40.74 | 875 | 125 | 7403 | 44 | 23.5625 | 30.5625 | 3369 | | X | A | 15 | SB6321 | W/996 |
| TSP6000-30TN | 48 | 24-H120-15 | 39.11 | 840 | 120 | 7403 | 44 | 23.5625 | 30.5625 | 3335 | | X | A | 15 | SB6321 | W/996 |
| TSP6000-30TT | 48 | 24-P140-15 | 45.63 | 980 | 140 | 7403 | 44 | 23.5625 | 30.5625 | 3403 | | X | A | 15 | SB6321 | W/996 |
| 44.5 x 24.6875 x 31 Compartment "A" | | | | | | | | | | | | | | | | |
| TSP6000-30TF | 48 | 24-D125-19 | 52.38 | 1125 | 125 | 7563 | 44.1875 | 25.5625 | 30.5625 | 4131 | | X | A | 15 | SB6321 | W/996 |
| TSP6000-30TN | 48 | 24-H120-19 | 50.28 | 1080 | 120 | 7563 | 44.1875 | 25.5625 | 30.5625 | 4090 | | X | A | 15 | SB6321 | W/996 |
| TSP6000-30TT | 48 | 24-P140-19 | 58.67 | 1260 | 140 | 7563 | 44.1875 | 25.5625 | 30.5625 | 4172 | | X | A | 15 | SB6321 | W/996 |
| 44.5 x 28.125 x 31 Compartment "B" | | | | | | | | | | | | | | | | |
| TSP6000-30TF | 48 | 24-D125-21 | 58.20 | 1250 | 125 | 7616 | 44 | 32.6875 | 30.5625 | 4676 | | X | A | 15 | SB6321 | W/996 |
| TSP6000-30TN | 48 | 24-H120-21 | 55.87 | 1200 | 120 | 7616 | 44 | 32.6875 | 30.5625 | 4629 | | X | A | 15 | SB6321 | W/996 |
| TSP6000-30TT | 48 | 24-P140-21 | 65.18 | 1400 | 140 | 7616 | 44 | 32.6875 | 30.5625 | 4723 | | X | A | 15 | SB6321 | W/996 |
| 44.5 x 33.75 x 31 Compartment "C" | | | | | | | | | | | | | | | | |
| TSP7000-33TF | 80 | 40-D125-9 | 38.80 | 500 | 125 | 9528 | 44 | 24.1875 | 30.5625 | | | X | A | 15 | SB6320 | |
| 44.5 x 24.75 x 31 | 80 | 40-H120-9 | 37.25 | 480 | 120 | 9528 | 44 | 24.1875 | 30.5625 | | | X | A | 15 | SB6320 | |
| Compartment "A" | 80 | 40-P140-9 | 43.46 | 560 | 140 | 9528 | 44 | 24.1875 | 30.5625 | | | X | A | 15 | SB6320 | |
| TSP7000-33TF | 80 | 40-D125-11 | 48.50 | 625 | 125 | 9531 | 44 | 27.625 | 30.5625 | 4065 | | X | A | 15 | SB6320 | |
| 44.5 x 28.1875 x 31 | 80 | 40-H120-11 | 46.56 | 600 | 120 | 9531 | 44 | 27.625 | 30.5625 | 4024 | | X | A | 15 | SB6320 | |
| Compartment "B" | 80 | 40-P140-11 | 54.32 | 700 | 140 | 9531 | 44 | 27.625 | 30.5625 | 4106 | | X | A | 15 | SB6320 | |
| TSP7000-33TF | 80 | 40-D125-13 | 58.20 | 750 | 125 | 9530 | 44 | 33.25 | 30.5625 | 4731 | | X | A | 15 | SB6320 | |
| 44.5 x 33.75 x 31 | 80 | 40-H120-13 | 55.87 | 720 | 120 | 9530 | 44 | 33.25 | 30.5625 | 4684 | | X | A | 15 | SB6320 | |
| Compartment "C" | 80 | 40-P140-13 | 65.18 | 840 | 140 | 9530 | 44 | 33.25 | 30.5625 | 4778 | | X | A | 15 | SB6320 | |
| TSP7000-33TF | 80 | 40-D125-15 | 67.90 | 875 | 125 | 9532 | 44 | 39.8125 | 30.625 | 4792 | | X | D | 22 | SB6320 | |
| 44.5 x 40.3125 x 31 | 80 | 40-H120-15 | 65.18 | 840 | 120 | 9532 | 44 | 39.8125 | 30.625 | 4744 | | X | D | 22 | SB6320 | |
| Compartment "D" | 80 | 40-P140-15 | 76.05 | 980 | 140 | 9532 | 44 | 39.8125 | 30.625 | 4840 | | X | D | 22 | SB6320 | |
| TSP7000-33TN | 72 | 18-D125-11 | 21.83 ea | 625 | 125 | 6E81 | 44 | 13 | 30.5 | 1832 | | X | A | 15 | SB6320 | |
| TSP7000-33TT | 72 | 18-H120-11 | 20.95 ea | 600 | 120 | 6E81 | 44 | 13 | 30.5 | 1814 | | X | A | 15 | SB6320 | |
| 44.5 x 13.5 x 31 | 72 | 18-P140-11 | 24.44 ea | 700 | 140 | 6E81 | 44 | 13 | 30.5 | 1850 | | X | A | 15 | SB6320 | |
| Compartment "B" See Note C | | | | | | | | | | | | | | | | |

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.

TURRET SIDE LOADER, TURRET STOCKPICKER (continued)

| Truck Model and Maximum Battery Size (Inches) | Volt | Battery Type | Capacity | | AH/ Pos. Plate | IST Tray No. | Battery Dimensions (in.) | | | Approx. Serv. Wt. (lbs.) | Cover | | Leads | | Standard Conn. |
|--|------|-----------------|-------------------|------|----------------------|--------------------|--------------------------|------------|-------------|--------------------------------|-------|----|-------|-----------------|-------------------|
| | | | 6 Hr. Rate KWH | A.H. | | | Length X | Width Y | Height Z | | Yes | No | Pos. | Length (in.) | |
| TSP7000-33TN | 72 | 18-D125-13 | 26.19 ea | 750 | 125 | 6E82 | 44 | 15.75 | 30.5625 | 2241 | | X | A | 15 | SB6320 |
| TSP7000-33TT | 72 | 18-H120-13 | 25.14 ea | 720 | 120 | 6E82 | 44 | 15.75 | 30.5625 | 2219 | | X | A | 15 | SB6320 |
| 44.5 x 33.75 x 31 Compartment "C" See Note C | 72 | 18-P140-13 | 29.33 ea | 840 | 140 | 6E82 | 44 | 15.75 | 30.5625 | 2263 | | X | A | 15 | SB6320 |
| TSP7000-33TN | 72 | 18-D125-15 | 30.56 ea | 875 | 125 | 6E83 | 44 | 19 | 30.5625 | 2641 | | X | A | 15 | SB6320 |
| TSP7000-33TT | 72 | 18-H120-15 | 29.33 ea | 840 | 120 | 6E83 | 44 | 19 | 30.5625 | 2615 | | X | A | 15 | SB6320 |
| 44.5 x 40.3125 x 31 Compartment "D" See Note C | 72 | 18-P140-15 | 34.22 ea | 980 | 140 | 6E83 | 44 | 19 | 30.5625 | 2667 | | X | A | 15 | SB6320 |

Note C: 72 volt TS and TSP models require two (2) 18 cell batteries

ea - KWH calculated for each 18-cell battery

H - Designates (H-Series battery type), Hydrasaver Product - Extended Watering Series.

Batteries listed are also available in the Max Power "P" Line which is a 10% increase of ampere hour capacity over the standard "D" Line. Refer to Table #2 of Selector Guide for "D" series to Max Power series cross reference table.

EAST PENN manufacturing co., inc.

Lyon Station, PA 19536-0147 • Phone: 610-682-6361 • Fax: 610-682-4212
www.dekabatteries.com • e-mail: epmmotve@eastpenn-deka.com

DISCLAIMER: When battery is installed in truck, battery restraints should be adjusted to prohibit movement of the battery to no more than 1/2" in a horizontal direction. Battery dimensions are $\pm 1/16"$. Battery weights may vary $\pm 5\%$. Counterweight must be added if the service weight stamped on

the battery is less than the minimum weight required on that particular model truck. The information is subject to change upon notice from equipment manufacturers or field experience. East Penn expressly denies any responsibility for the accuracy of this information. While East Penn has and continues to

make every effort to accurately catalog the information in this document, East Penn disclaims any warranties, expressed or implied, for the accuracy of the information in this document. East Penn denies any liability for damages as a consequence of using the information in this document.